

Epson EasyMP Network Projection

You can project your computer screen via the network using the Epson Projection Software, also known as EasyMP.



NOTE: Ensure your PC is connected to the OIST Wi-Fi Network. If using video or sound, please use the wired connection for best results.

Install Projector Software

1. Using your web browser, go to <http://goo.gl/WLkFLg>, or search for “epson easymp” on Google.
2. Download and install the version which is appropriate for your operating system.

Connect to Projector

1. Turn on the Projector, and press the **LAN** button on the projector's remote control.
2. Launch the Epson EasyMP Network software.
3. In the **Connection Mode** window, select **Advanced Connection Mode**, and click the checkbox so this message doesn't appear again.
NOTE: A message stating, “No Projector was found” may appear. Click **OK**.
4. Click the **Manual search** tab, and enter the projector's IP address in the **Manual search** dialog box.
NOTE: The IP address is displayed on the projector screen after pressing the **LAN** button on the remote control.
5. Click the checkbox next to the Projector Name, and click **Connect**, to start projecting your screen.
TIP: To avoid entering the IP address each time, you can save each projector you connect to in your profile by selecting the projector and clicking the **Save in the profile** button.



EasyMP Toolbar Projector Controls

This toolbar appears when you connect to the projector.



- Use the **Stop** button to blacken the screen but still stay connected
- Use the **Pause** button to freeze the screen
- Use the **Presentation Mode** button to project only the PowerPoint / Keynote Slide Show running on your PC. A black screen is projected when the Slide Show is not playing, so you may start presentations smoothly without projecting unnecessary images.

Contact AV Services at av@oist.jp or 11534, to request assistance or report a fault.