# Renewable energy forecast error

### The Problem

In renewable energy, utility operators use forecast models to predict energy fluctuations over a future time horizon to account for operating reserves, and protect grid infrastructure from instabilities. These models are of limited accuracy and as a result operating reserves may be inadequate or overprovided, and grid instabilities may be caused by under or over production of power. Forecasting enables operators to manage varying levels of power generation and operate equipment efficiently and traders to make marketing decisions. However, it has been reported by an operator that over the 5 year period 2008-2013 wind power failed to meet forecast 58% of the time.

# 20 proceding forecasts current forecast characteristics and solutions are conservations and solutions are conservations.

Figure showing measured power (blue), 5-day forecast (red), preceding forecasts (green) and envelope of confidence for 5-day forecast (shaded region). As the horizon is increased, the confidence falls. Figure courtesy EWC Weather Consult GmbH.

### **The Solution**

This invention makes it possible to quantify two errors, used to qualify and improve forecast models, protecting against losses in revenue and grid instabilities caused by energy fluctuations.

### **Applications**

- Wind power
- Ocean power
- Solar power

### **Benefits**

- Minimal data is required to perform forecast error analysis; time series for actual power generated and forecast power
- Applicable to any data sampling rate

### **Keywords**

Renewable energy, wind power, ocean power, solar power, forecast, operating reserves, penalties, energy markets, energy spot markets, grid instability

# **Opportunity**

- OIST welcomes inquiries from parties interested in licensing this technology.
- A proof of concept based on real-world data is available to demonstrate feasibility.
- A proof of concept based on the data of the prospective licensee or customer thereof is available after execution of an NDA.

### **Patent protection**

This technology is protected by an International Patent Application: PCT/JP2016/000950.

## For more information

Contact the Technology Licensing Section at <a href="mailto:bdtl@oist.jp">bdtl@oist.jp</a> or +81-(0)98-966-8937